



50 KG ELECTRONIC SCALES



Non-contractual photo.

OVERVIEW

Professional-quality electronic scales, sturdy and usable either in or outside of its protective carry-case.

The scales can be fitted optionally with a programmable loading kit for loading or recovering refrigerants.

The waterproof liquid crystal control module is humidity-resistant. It can be separated from the tray, to which it is attached by a 15 m coiled cable, and it has a built in low battery indicator.

The tray is fitted with a built-in spirit level.

TECHNICAL SPECIFICATIONS

Standard graduation (in compliance with the Institut National des Standards et Technologies)

Automatic switch off in the event of an interruption in refrigerant flow

Suspend mode allowing for a change of bottle during filling

Protection against overloading

1.3 cm liquid crystal screen - bold, dark figure: easy reading in very bright environments

Load capacity	50 kg max.
Resolution	0.01 kg
Precision	± 0.015 kg or 0.1% of reading
Total weight	4.1 kg
Size of carry-case (mm)	394 (L) x 311 (W) x 83 (h)
Module screen	High resolution LCD
Module keyboard	Membrane with metallic tactile domes
Size of tray	228 x 228 mm
Battery life	Approximately 25 hours of continuous use
Battery	9 V alkaline
Operating temperature	0° to +50°C
Storage temperature	-20° to +70°C

The information in this article is the result of our studies and of our experience. It is given in good faith but cannot in any way constitute a guarantee from us, or mean that we accept liability, especially in the case of infringement of third parties or of failure by users of our products to abide with the relevant current regulations.

